



CONNECTORIZED JUNCTION



P/N JDVP-P2P

DESCRIPTION

Device for the junction of the LN-SRP2P-300 prewired sensor-strings. It is provided with a UV resistant housing, two easy-plug sockets and a fixing support.

UV resistant polyamide case with connectors and disk-shaped fixing support used to make Junction for Serir P2P connectorized LN-SRP2P-300 string.

INSTALLATION

The product BOX-P2P is suitable for outdoor applications, protected against splashed water (IP-44) and made of a fibreglass reinforced polyester material (self-extinguishing and flame retardant). Here below are shown the preliminaries for the SERIR P2P connectorized string junction.

1. Install the disk-shaped fixing support with the arrow down on the fence using tie wraps provided and the holes present on the disk.
2. Join the two prewired string tightening the connector to the JDVP-P2P junction to ensure IP68.
3. Attach the JDVP-P2P to the Fixing disk with the cable inputs down and slide down on the fixing disk.
4. Rotate the junction so that it is oriented horizontally.

INSTALLATION JDVP-P2P



COMPLIANCES

JUNCTION

- DIRETTIVA 2014/30/EU

SOCKET

- CEI 60512-4, UL94-V0, UL 1977, MIL-C-26482, MIL-STD1344, ROHS



TECHNICAL FEATURES

- GROSS WEIGHT: 123 g
- CASE (JUNCTION)
- HOUSING DIMENSION: 90 x 56 x 43 mm (L x L x H)
- FIXING PLATE: 90 x 8 mm (Ø x L)
- OPERATING TEMPERATURE: -40 ÷ +80 °C
- RELATIVE HUMIDITY: <95% non condensante
- MATERIAL: glass fiber reinforced polyamide
- IP RATING: IP54
- COLOUR: black

CONNECTOR (SOCKET)

- CONNECTOR TYPE: presa circolare maschio a 4 poli
- DIMENSION: 27 x 33,9 mm (Ømax x L)
- OPERATING TEMPERATURE: -40 ÷ +80 °C
- UMIDITÀ RELATIVA: <95% non condensante
- MATERIAL: thermoplastic resistant to UV rays, mineral oils, hydrocarbons and acids
- IP RATING: IP68 (if correctly fastened with the relevant plug)
- COLOUR: black



TO BE USED FOR THE JUNCTION OF THE SENSOR-STRINGS PROVIDED WITH EASY-PLUG CONNECTORS.



TO JOIN THE UNCONNECTORIZED SENSOR-STRINGS, THE JBX-P2P CASE MUST BE USED.

DEA Security S.r.l.

Via Bolano, snc - 19037 Santo Stefano di Magra (SP) - tel. +39 0187 699233 - fax +39 0187 697615

VAT NO.: IT00291080455

www.deasecurity.com - dea@deasecurity.com

