

SNO 6011R 2 MEGAPIXEL FULL HD NETWORK IR CAMERA

TECHNICAL SPECIFICATIONS

SECURITY SYSTEM

DIVISION – 28 ELECTRONIC SAFETY AND SECURITY

LEVEL 1 28 20 00 ELECTRONIC SURVEILLANCE

LEVEL 2 28 23 00 VIDEO SURVEILLANCE

LEVEL 3 28 23 29 VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS

PART 2 – PRODUCTS

2.01 GENERAL

- A. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free (U.S. and Canada), 24-hour technical assistance program (TAP) from the manufacturer. The TAP shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.

2.02 SNO-6011R 2 MEGAPIXEL FULL HD NETWORK IR CAMERA

- A. The camera shall be of a bullet type for internal or external use. The camera shall be dark grey in appearance.
- B. The camera shall be tested to IP66 for ingress protection.
- C. The camera shall feature an adaptive Infrared illumination system giving a viewable distance of 10m in complete darkness.
- D. The network camera shall feature up to 2 Mega Pixel Full HD (1080p) resolution in a 16:9 format. 4:3 format shall also be available in smaller resolutions.
- E. The camera should be capable of capturing and transmitting an image size of 1920 x 1080 at 30 images per second.
- F. The camera shall be capable of simultaneously streaming two 1080p video streams, each at 30 images per second.
- G. The camera shall feature a day / night mode that incorporates an infrared cut filter removal mechanism for true colour reproduction and the best possible low light performance.
- H. The camera shall feature a fixed 3.8mm lens.
- I. The camera shall feature Wide Dynamic Range with a gain of 120db. This feature will work at 30 images per second at 1920 x 1080 resolution. The WDR function shall feature an adaptive motion system to eliminate motion blur.
- J. The camera shall feature a high performance 2D & 3D noise reduction that automatically adapts the type of technology used according to movement in the field of view. 2D noise reduction compares adjacent pixels while 3D technology compares the same pixel in the previous and subsequent images, giving a higher level of detail. When the camera detects movement in a region of the image it will apply 2D noise reduction to that area and 3D noise reduction to the remainder of the image.
- K. The camera shall feature an automatic back light compensation technology that detects and enhances dark areas in the field of view and increases the gain in those areas.
- L. The camera shall feature built in license free video analytics functions including line crossing, appear/disappear, audio detection, camera tamper (scene change) and enter/exit a predefined zone.
- M. The camera shall feature advanced motion detection with definable detection areas, minimum / maximum object size definition and a learning algorithm that ignores false alarms such as trees and waves on water.
- N. The camera shall support Multi Cropping technology to allow video profiles to be set up with a reduced area of the overall field of view of the camera.

- O. The camera shall feature a face detection technology that can be used to create an event whenever there is a face or multiple faces in the image. The technology should be able to detect 32 faces simultaneously.
- P. The camera shall feature 32 privacy zone mask areas.
- Q. The camera shall feature a smart codec that can use a higher quality compression for regions of interest in the image, thereby prioritising the encoding of the most important areas of the field of view.
- R. The camera shall feature a Digital Image Stabilisation function.
- S. The camera shall feature a backlight compensation technology that can be used to manually select an area of high brightness in the field of view and adjust the gain in that area.
- T. The network camera shall provide video transmission in an open format with H.264 or MJPEG compression.
- U. The camera shall support ONVIF profile S for operation with 3rd party systems.
- V. The camera shall be capable of simultaneously transmitting multiple video streams of different resolution, compression, frame-rate and compression settings.
- W. The network camera should be configurable through a built in web server that can be accessed via standard browsers including Internet Explorer, Firefox, Chrome & Safari.
- X. The cameras shall support micro SD, SDHC & SDXC flash memory card for recording video footage on event, network loss or continuously.
- Y. The camera shall provide a customizable on-screen display (OSD) which shall be available in English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Romanian, Serbian, Dutch, Croatian, Hungarian, Greek, Finnish, Norwegian.

2.03 CAMERA

A. Imaging Device	1/ 2.8" PS Exmore 2.38M CMOS(IMX136)
B. Total Pixels	1,952(H) x 1,236(V)
C. Effective Pixels	1,944(H) x 1,224(V)
D. Scanning System	Progressive
E. Min. Illumination	
1. Color	0.3 Lux (F2.0, 50IRE), 0.03Lux (2sec, 50IRE)
2. B/W	0 Lux (IR LED on)
F. S / N Ratio	50dB
G. Video Output	CVBS : 1.0 Vp-p / 75Ω composite, 704x480(N), 704x576(P)

2.04 LENS TYPE

A. Mount Type	Board-in type
B. Focal Length(Zoom Ratio)	3.8mm Fixed
C. Max. Aperture Ratio	F2.0
D. Angular Field of View	H : 84.5°, V : 45.8°, D : 98.8°)
E. Min. Object Distance	0.5M
F. Focus Control	Manual

2.05 OPERATION

A. Camera Title	Off / On (Displayed up to 45 characters)
B. Day & Night	Auto (ICR) / Color / B/W
C. Backlight Compensation	Off, BLC
D. Wide Dynamic Range	Off, / On (120dB)
E. Contrast Enhancement SSDR	On, Off
F. Digital Noise Reduction SSNR III	On, Off
G. Motion Detection	Off / On (4ea 4 Points Polygonal zones)
H. Privacy Masking	Off / On (32ea Polygonal zones)
I. Gain Control	Off / Low / Middle / High
J. White Balance	ATW / AWC / Manual / Indoor / Outdoor

K. Electronic Shutter Speed	Auto / A.FLK / Manual (1/30 ~ 1/12,000sec)
L. Flip / Mirror	Off, On
M. Intelligent Video Analytics	Tampering, Virtual Line, Enter/Exit, Appear / Disappear, Face Detection, with Metadata
N. Alarm I/O	Input 1ea
O. Alarm Triggers	Motion detection, Tampering Detection, Face Detecton, Video Analytics, Alarm Input, Network Disconnection
P. Alarm Events	File upload via FTP and E-Mail Notification via E-Mail,
Q. Defog	Auto/Manual/Off
R. Viewable Length	15m

2.06 NETWORK PROTOCOL

A. Ethernet	RJ-45 (10/100Base-T)
B. Video Compression Format	H.264(MPEG-4 part 10/AVC), MJPEG
C. Resolution	1920x1080 /1600x1200/ 1280x1024 /1280x960 / 1280x720 / 1024x768 / 800x600 / 800x450 / 640x480 / 640x360 / 320x240 / 320x180
D. Max. Framerate	Max 30fps at all resolutions
1. H.264	1920x1080 /1600x1200/ 1280x1024 /1280x960 / 1280x720 / 1024x768 : Max. 15 fps
2. Motion JPEG	800x600 / 800x450 / 640x480 / 640x360 / 320x240 / 320x180 : Max. 30fps
E. Video Quality Adjustment	Compression level, Target bit rate level control
1. H.264	Quality level control
2. MJPEG	
F. Bitrate Control Method	CBR or VBR
1. H.264	VBR
2. MJPEG	Multiple Streaming (Up to 10 Profiles)
G. Streaming Capability	IPv4, IPv6
H. IP	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
I. Protocol	HTTPS(SSL) Login Authentication
J. Security	Digest Login Authentication
	IP Address Filtering
	User access Log
	802.1x Authentication
K. Streaming Method	Unicast, Multicast
L. Max. User Access	15 users at Unicast mode
M. Memory Slot	micro SD/SDHC/SDXC
	- motion Images recorded in the SDX/SDHC/SD memory card can be downloaded.
N. ONVIF Conformance	ONVIF Profile S, HTTP API v2.0, SVNP 1.2
O. Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Denish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek, Finnish, Norwegian
P. Web Viewer	Windows XP / VISTA / 7 / 8, MAC OS X 10.7
1. Supported OS	Microsoft Internet Explorer (Ver. 7~10),
2. Supported Browser	Mozilla Firefox (Ver. 9~19),
	Google Chrome (Ver. 15~25),

	3. Central Management Software	Apple Safari (Ver. 6.0.2(Mac OS X 10.8, 10.7 Only), 5.1.7) SmartViewer 4.0
2.07	ELECTRICAL	
	A. Voltage	PoE(IEEE802.3af)
	B. Consumption	Max. 8.5W
2.08	ENVIRONMENTAL SPECIFICATIONS	
	A. Operating Temperature	-10°C ~ +55°C
	B. Operating Humidity	Less than 90% RH
	C. Ingress Protection	IP66 Grade (Waterproof)
2.09	PHYSICAL SPECIFICATIONS	
	A. Dimension(WxHxD)	68.4*262.2
	B. Weight	330g
	C. Color	Dark Gray(Plastic)
2.10	CERTIFICATIONS	
	A. CE mark	
	B. FCC mark	
2.11	WARRANTY	
	A. 3 years, parts and labor.	