



Hanwha Techwin is a global leading supplier of solutions for IP and analog video surveillance. Building on the company's history of innovation, Hanwha Techwin is dedicated to providing systems solutions with the highest levels of performance, reliability and cost-effectiveness. Hanwha Techwin is committed to the continued development of innovative systems products for professional security applications.

For additional information, visit <http://www.hanwha-security.com/>

## 5 MP NETWORK DOME CAMERA

### DIVISION 28 – ELECTRONIC SAFETY AND SECURITY

#### Notes to Specifier:

1. Where several alternative parameters or specifications exist, or where, the specifier has the option of inserting text, such choices are presented in **<bold text>**.
2. Explanatory notes and comments are presented in **colored** text.

**Important:** See further notes on the following page.

**Important Note to Security Systems Specifiers**

CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. The following is a guide to the MasterFormat numbers relevant to the product referenced in this specification.

**Primary Specification Area:****MasterFormat 2014:**

|          |                                               |
|----------|-----------------------------------------------|
| 28 20 00 | Electronic Surveillance                       |
| 28 23 00 | Video Surveillance                            |
| 28 23 29 | Video Surveillance Remote Devices and Sensors |

**MasterFormat 2016:**

|          |                      |
|----------|----------------------|
| 28 20 00 | Video Surveillance   |
| 28 2x xx | Surveillance Cameras |
| 28 2x xx | IP Cameras           |

**Related Requirements:****MasterFormat 2014:**

|          |                                                          |
|----------|----------------------------------------------------------|
| 27 20 00 | Data Communications                                      |
| 28 23 13 | Video Surveillance Control and Management Systems        |
| 28 23 16 | Video Surveillance Monitoring and Supervisory Interfaces |
| 28 23 19 | Digital Video Recorders and Analog Recording Devices     |
| 28 23 23 | Video Surveillance Systems Infrastructure                |

**MasterFormat 2016**

|             |                                                         |
|-------------|---------------------------------------------------------|
| 27 15 01.xx | Video Surveillance Communications Conductors and Cables |
| 27 20 00    | Data Communications                                     |
| 28 05 xx.xx | PoE Power Sources for Electronic Safety and Security    |
| 28 05 xx    | Storage Appliances for Electronic Safety and Security   |
| 28 05 xx.xx | Network Video Recorders                                 |
| 28 05 xx    | Cyber Requirements for Electronic Safety and Security   |
| 28 05 xx    | Safety and Security Network Communications Equipment    |
| 28 2x 00    | Video Management System                                 |

## 5 MP NETWORK DOME CAMERA

### PART 1 GENERAL

#### 1.01 SUMMARY

- A. Section includes a 5 MP IP video camera
- B. Product - A 5 MP IP video camera with multi-streaming (H.265, H.264 and MJPEG) capability in a IK10 rated dome body
- C. Related Requirements

---

**Refer to MasterFormat notes at the beginning of this document to select requirements specific to the MasterFormat version being used in the specification.**

---

#### 1.02 REFERENCES

##### A. Abbreviations

- |           |                                     |
|-----------|-------------------------------------|
| 1. AGC    | Auto Gain Control                   |
| 2. AES    | Advanced Encryption Standard        |
| 3. API    | Application Programming Interface   |
| 4. ARP    | Address Resolution Protocol         |
| 5. AWB    | Auto White Balance                  |
| 6. BLC    | Back light compensation             |
| 7. CBR    | Constant Bit Rate                   |
| 8. CVBS   | Composite Video Blanking and Sync   |
| 9. DHCP   | Dynamic Host Configuration Protocol |
| 10. DNR   | Digital Noise Reduction             |
| 11. DNS   | Domain Name Server                  |
| 12. DDNS  | Dynamic Domain Name Server          |
| 13. DSCP  | Differentiated Services Code Point  |
| 14. fps   | frames per second                   |
| 15. FTP   | File Transfer Protocol              |
| 16. GOV   | Group of Video                      |
| 17. GUI   | Graphical User Interface            |
| 18. HD    | High Definition                     |
| 19. HTTP  | Hypertext Transfer Protocol         |
| 20. HTTPS | Secure HTTP                         |
| 21. ICMP  | Internet Control Message Protocol   |
| 22. IGMP  | Internet Group Management Protocol  |
| 23. IP    | Internet Protocol                   |
| 24. IR    | Infrared                            |
| 25. JPEG  | Joint Photographic Experts Group    |
| 26. LAN   | Local Area Network                  |

|            |                                            |
|------------|--------------------------------------------|
| 27. LED    | Light Emitting Diode                       |
| 28. LDC    | Lens Distortion Correction                 |
| 29. LLDP   | Link Layer Discovery Protocol              |
| 30. LPR    | License Plate Recognition                  |
| 31. MJPEG  | Motion JPEG                                |
| 32. MP     | Megapixel                                  |
| 33. MPEG   | Moving Pictures Experts Group              |
| 34. NAS    | Network Attached Storage                   |
| 35. NTP    | Network Time Protocol                      |
| 36. NVR    | Network Video Recorder                     |
| 37. PIM-SM | Protocol Independent Multicast-Sparse Mode |
| 38. PoE    | Power over Ethernet                        |
| 39. PPPoE  | Point to Point Protocol over Ethernet      |
| 40. QoS    | Quality of Service                         |
| 41. RTP    | Real-Time Transport Protocol               |
| 42. RTCP   | Real-Time Control Protocol                 |
| 43. RTSP   | Real-Time Streaming Protocol               |
| 44. SDK    | Software Development Kit                   |
| 45. SFP    | Small Form factor Pluggable                |
| 46. SMTP   | Simple Mail Transfer Protocol              |
| 47. SNMP   | Simple Network Management Protocol         |
| 48. SSDR   | Super Smart Dynamic Range                  |
| 49. SSNR   | Super Smart Noise Reduction                |
| 50. SSL    | Secure Sockets Layer                       |
| 51. TCP    | Transmission Control Protocol              |
| 52. UDP    | User Datagram Protocol                     |
| 53. UPnP   | Universal Plug and Play                    |
| 54. VBR    | Variable Bit Rate                          |
| 55. VMS    | Video Management System                    |
| 56. WDR    | Wide Dynamic Range                         |

## B. Reference Standards

1. Network - IEEE
  - a. 802.3 Ethernet Standards
  - b. 802.1x Port-based Network Access Control
  - c. IPv4 IP addressing version 4
  - d. IPv6 IP addressing version 6
  - e. QoS Quality of Service
2. Video
  - a. ISO / IEC 23008-2:2013, MPEG-H Part2 (ITU H.265, HEVC)
  - b. ISO / IEC 14496-10, MPEG-4 Part 10 (ITU H.264)

- c. ISO / IEC 10918 – JPEG
- d. ONVIF – Profile S / G
- 3. EMC & Safety
  - a. FCC 47 CFR Part 15 Subpart B
    - 1) ANSI C63.4-2014 Class A
  - b. IC Regulation ICES-003:2016
    - 1) ANSI C63.4-2014 Class A
  - c. CE EMC-Directive 2014/30/EU
    - 1) EN 55032:2015 Class A
    - 2) EN 50130-4:2011+A1:2014
  - d. VCCI-CISPR 32: Class A
  - e. AS/NZS CISPR32:2015 Class A
  - f. UL listed
  - g. CE EN 50581:2012 (hazardous substances)
- 4. Ingress Protection and Vandal Resistance
  - a. ANSI / IEC60529 – Degrees of Protection Provided by Enclosures – IP52
  - b. IEC EN 62262 - Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts : IK10
  - c. IEC 60068-2-75 : IK10
- C. Definitions
  - 1. GOV (Group of Video object planes) – A set of video frames for H.264 and H.265 compression, indicating a collection of frames from the initial I-Frame (key frame) to the next I-Frame. GOV consists of two kinds of frames in video surveillance setup: I-Frame and P-Frame.
  - 2. Dynamic GOV – Dynamic assignment of GOV length based on the complexity of the scene to efficiently manage bitrate of the video stream and reduce the storage required.
  - 3. Multi-exposure wide dynamic range – Operation which automatically adjusts shutter speed to provide a wide range between dark and light areas visible at the same time, preventing backlighting issues. Long exposure is used for dark areas and a short exposure is used in bright areas.
  - 4. Dynamic fps – Dynamic assignment of fps (frames per seconds) based on the movement of object(s) in the scene to efficiently manage bitrate of the video stream and reduce the storage required.
  - 5. WiseStream – Technology that controls quantization parameter, fps, and GOV length in H.265 and H.264 to efficiently manage bitrate of the video stream and reduce the storage required.

### 1.03 SUBMITTALS

- A. Product Data
  - 1. Manufacturer's printed or electronic data sheets
  - 2. Manufacturer's installation and operation manuals
  - 3. Warranty documentation

### 1.04 QUALIFICATIONS

- A. Manufacturer shall have a minimum of five years' experience in producing IP video equipment.
- B. Installers shall be trained and authorized by the Manufacturer to install, integrate.

#### **1.05 DELIVERY, STORAGE AND HANDLING**

- A. Deliver the camera in the manufacturer's original, unopened, undamaged container with identification labels intact.
- B. Store the camera in a temperature environment specified in section 2.04 Detailed Specification, protected from mechanical and environmental conditions as designated by the manufacturer.

#### **1.06 WARRANTY, LICENSING AND SUPPORT**

- A. Manufacturer shall provide at least a limited 3 year warranty for the product to be free of defects in material and workmanship.
- B. Manufacturer shall provide embedded camera video analytics free of license charges.

END OF SECTION

## **PART 2 PRODUCTS**

### **2.01 EQUIPMENT**

- A. Manufacturer: Hanwha Techwin  
<http://www.hanwha-security.com/>
- B. Model XND-8081VZ
- C. Alternates: None

### **2.02 GENERAL DESCRIPTION**

- A. Video Compression and Transmission – The camera shall have the following properties relating to the video signals it produces.
  - 1. H.265, H.264 and MJPEG compression, each derived from a dedicated encoder and capable of being streamed independently and simultaneously.
    - a. H.265 and H.264 – maximum of 30fps at all resolution
    - b. MJPEG – maximum of 30fps
  - 2. The camera shall be able to configure up to 10 independent video stream profiles with differing encoding, quality, frame rate, resolution, and bit rate settings.
  - 3. The camera shall be able to configure various resolution selections.
    - a. 16:9 aspect ratio : 2560 x 1440, 1920 x 1080, 1280 x 720, 800 x 448, 640 x 360
    - b. 4:3 aspect ratio : 2560 x 1920, 1600 x 1200, 1280 x 960, 1024 x 768, 800 x 600, 640 x 480, 320 x 240,
    - c. 5:4 aspect ratio : 1280 x 1024, 720 x 576,
    - d. 3:2 aspect ratio : 720 x 480
  - 4. The camera shall support unicast video streaming up to 20 users.
  - 5. The camera shall support multicast video streaming
  - 6. The camera shall be able to configure Dynamic DNS (DDNS). DDNS shall be provided with no additional cost by the manufacturer.
  - 7. The camera shall provide WiseStream II, Dynamic GOV and Dynamic fps to efficiently manage bit rate of the video stream and reduce storage.
- B. Camera – The camera device shall have the following physical and performance properties:
  - 1. IK10 rated for protection against impacts.
  - 2. True day/night operation with removable IR cut filter
    - a. Low light level operation to 0.07 lux at F1.3 in color mode and 0.007 lux at F1.3 in black and white mode.
  - 3. The camera shall be able to produce clear images in highly contrast scenes with multi-exposure wide dynamic range up to 120dB.
  - 4. The camera shall support digital noise reduction using both 2D and 3D noise reduction technology.
  - 5. The camera shall be able to configure 32 privacy masking areas with polygons.
  - 6. The camera shall have the defog feature to remove foggy scene which can be triggered automatically from the fog detection event.

7. The camera shall provide video display on smart phone (iPhone, Android) to adjust viewing angle, rotation and focus.
- C. Intelligence and Analytics – The camera shall have a suite of intelligent analytic functions.
  1. Motion detection with 8 definable detection areas with 8 point polygonal zones, and minimum/maximum object size.
  2. Detection of logical events of specified conditions from the camera's video
    - a. Tampering, Loitering, Directional Detection, Virtual Line, Enter/Exit, (Dis)Appear
    - b. Defocus Detection, Fog Detection, Shock Detection
    - c. Motion Detection, Digital Auto Tracking, Face Detection
    - d. Audio Detection, Sound Classification
    - e. Audio playback on event
  3. Detection and classification of the following sound.
    - a. Scream
    - b. Gunshot
    - c. Explosion
    - d. Crashing glass
- D. Interoperability – The camera shall be ONVIF Profile S and G compliant.
- E. The camera shall possess the following further characteristics:
  1. Built-in web server, accessed via non-plugin browsers including Google Chrome, IE11, MS Edge, Mozilla Firefox and Apple Safari.
  2. Micro SD/SDHC/SDXC memory card with configurable pre-alarm and post-alarm recording intervals
  3. NAS recording option with configurable pre-alarm and post-alarm recording intervals
  4. Alarms and notifications
    - a. alarm notification triggers:
      - 1) Alarm input
      - 2) Motion detection
      - 3) Video & Audio analytics
      - 4) Network disconnect
    - b. available notification means upon trigger:
      - 1) File Upload via FTP and E-mail
      - 2) Notification via E-mail
      - 3) Local storage (SD / SDHC / SDXC) or NAS recording at event triggers
      - 4) External output
  5. Pixel Counter available in the web viewer.
  6. PoE capable including heater by PoE
  7. IP52, IK10 capable

### 2.03 CAMERA SOFTWARE

- A. The camera shall have a built in web server which supports non-plugin browsers including Google Chrome, IE11, MS Edge, Mozilla Firefox and Apple Safari from a PC or Mac.



- B. The web viewer shall provide a monitoring screen which displays live camera video and simultaneously provides same-screen access to the following functions:
  - 1. Live view window size
  - 2. Resolution setting
  - 3. Image (snapshot) capture
  - 4. Manual recording to SD or NAS
  - 5. Audio/microphone control
  - 6. Access recorded data playback and camera configuration menus
  - 7. Digital PTZ
- C. The web viewer shall provide a playback screen which provides access to the following functions:
  - 1. Recorded data search using date and time range
  - 2. Recorded data search using event type
  - 3. Play a recorded video by event triggering
  - 4. Set resolution
  - 5. Play audio if present
  - 6. Generate a backup copy of saved video data
- D. The web viewer shall provide a setup screen which provides access to the following configuration settings and functions in the camera:
  - 1. Digital video profile to include compression type, maximum or target bit rate, frame rate, multicast parameters, and crop encoding area
  - 2. User profile to include password, access level, authentication
  - 3. Date and time
  - 4. Network settings and IP version
    - a. DDNS
    - b. IP filtering
    - c. SSL, including certificate management
    - d. 802.1x authentication
    - e. Quality of Service settings
    - f. SNMP to include version selection and settings
    - g. Auto IP configuration
  - 5. Video setup
    - a. Flip / mirror mode
    - b. Video output type
    - c. Privacy zone.
  - 6. Audio setup to include source, audio codec type, gain and bit rate.
  - 7. Camera settings to configure image preset, sensor frame capture, dynamic range, white balance, back light, exposure, day/night operation, on-screen display, sharpness, contrast, color level and lens distortion correction.
  - 8. Event detection setup to configure notification parameters, recording rules, time schedule, tamper protection, motion detection and event triggers
  - 9. System function to control reboot, upgrade, check system and event logs and application (SDK) management

## 10. View profile information

## E. Client requirements

1. Acceptable Operating Systems: Windows 7 / 8.1 / 10, MAC OS X 10.9, 10.10, 10.11, 10.12
2. Acceptable browsers:
  - a. Non-plugin WebViewer Google Chrome 63, IE11, MS Edge 41,  
Mozilla Firefox 57(Window 64bit only), Safari 11(Mac OS X only)

**2.04 DETAILED SPECIFICATIONS**

## A. Video

1. Imaging device 1/1.8" 6MP CMOS
2. Image Pixels Total: 3,096(H) x 2,094(V), effective: 2,616(H) x 1,976(V)
3. Scanning Progressive
4. Minimum Illumination Color: 0.07Lux (F1.2, 1/30sec), B/W: 0.007Lux (F1.2, 1/30sec)
5. S/N Ratio 50dB

## B. Lens:

1. Focal length 3.6~9.4mm(2.6x) motorized varifocal
2. Max. Aperture Ratio F1.2(Wide)~2.4(Tele)
3. Field of View [Wide] H: 102.5°, V: 74.2°, D: 135.5°  
[Tele] H: 38.7°, V: 29.0°, D: 48.6°
4. Min. Object Distance 0.5m (1.64ft)
5. Focus Control Simple focus/Manual (Remote control via network)
6. Lens Type DC Auto Iris, P-Iris
7. Mount Type Board-in Type

## C. Pan &amp; Tilt &amp; Rotate

1. PTR Range  $\pm 175^\circ$  /  $0\sim 85^\circ$  /  $\pm 175^\circ$
2. PTR Control Remote adjustment(Max. 200 cycles)

## D. Operational Functions

1. Camera Title Off / On (Displayed up to 85 characters)
  - a. W/W English / Numeric / Special characters
  - b. China English / Chinese / Numeric / Special characters
  - c. Common Multi-line (Max. 5), Color (Grey/Green/Red/Blue/Black/White),  
Transparency, Auto scale by resolution
2. Day/Night Setting Auto (ICR) / Color / B/W / External / Schedule
3. Backlight Compensation Off / BLC / HLC / WDR
4. WDR 120dB
5. Contrast Enhancement Off / On (SSDR)
6. Digital Noise Reduction Off / On (SSNR5 : 2D+3D Noise filter)
7. Digital Image Stabilization Off / On (built-in Gyro sensor)
8. Defog Off / Manual / Auto

|                                |                                                                                                                                                                                                                                                                                                                                                                    |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9. Motion Detection            | Off / On (8ea, 8-point polygonal), Handover                                                                                                                                                                                                                                                                                                                        |
| 10. Privacy Masking            | Off / On (32 zones, polygonal)<br>- Color: Grey / Green / Red / Blue / Black / White<br>- Mosaic                                                                                                                                                                                                                                                                   |
| 11. Gain Control               | Off / Low / Middle / High                                                                                                                                                                                                                                                                                                                                          |
| 12. White Balance              | ATW / AWC / Manual / Indoor / Outdoor<br>(Including Mercury and Sodium)                                                                                                                                                                                                                                                                                            |
| 13. Lens Distortion Correction | Off/On (5 Levels with Min/Max)                                                                                                                                                                                                                                                                                                                                     |
| 14. Electronic Shutter Speed   | Min / Max / Anti-flicker (2 ~ 1/12,000sec)                                                                                                                                                                                                                                                                                                                         |
| 15. Digital Zoom               | 24x                                                                                                                                                                                                                                                                                                                                                                |
| 16. Digital PTZ                | Support (Preset, Group)                                                                                                                                                                                                                                                                                                                                            |
| 17. Image Rotation             | Flip: Off / On<br>Mirror: Off / On<br>Hallway view: 0° / 90° / 270°                                                                                                                                                                                                                                                                                                |
| 18. Alarm I/O                  | Input 1ea / Output 1ea                                                                                                                                                                                                                                                                                                                                             |
| 19. Alarm Triggers             | Alarm Input, Motion Detection, Video & Audio Analytics,<br>Network Disconnection                                                                                                                                                                                                                                                                                   |
| 20. Alarm Events               | File Upload via FTP and E-mail, Notification via E-mail,<br>Local storage (SD/SDHC/SDXC) or NAS recording,<br>External output, DPTZ Preset                                                                                                                                                                                                                         |
| 21. Pixel Counter              | Support                                                                                                                                                                                                                                                                                                                                                            |
| 22. Storage                    | Micro SD/SDHC/SDXC 512GB (256GB x 2 slots) , NAS support                                                                                                                                                                                                                                                                                                           |
| 23. Intelligent Analytics      | Tampering, Loitering, Directional Detection, Defocus Detection,<br>Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Audio Detection,<br>Face Detection, Motion Detection, Digital Auto Tracking,<br>Sound classification (Scream/Gunshot/Explosion/Crashing glass)<br>Shock detection, Heatmap, People counting, Queue management,<br>Audio Playback on event |
| 24. Video Out (Installation)   | USB: Micro USB type B, 1280 x 720                                                                                                                                                                                                                                                                                                                                  |
| E. Video Streams               |                                                                                                                                                                                                                                                                                                                                                                    |
| 1. Video compression           | H.265, H.264, MJPEG                                                                                                                                                                                                                                                                                                                                                |
| 2. Resolution                  | 2560 x 1920, 2560 x 1440, 1920 x 1080, 1600 x 1200,<br>1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768, 800 x 600,<br>800 x 448, 720 x 576, 720 x 480, 640 x 480, 640 x 360, 320 x 240                                                                                                                                                                             |
| 3. Maximum Framerate           |                                                                                                                                                                                                                                                                                                                                                                    |
| a. H.265 / H.264               | Max. 30fps at all resolutions                                                                                                                                                                                                                                                                                                                                      |
| b. MJPEG                       | Max. 30fps                                                                                                                                                                                                                                                                                                                                                         |
| 4. Smart Codec                 | Manual Mode (area-based : 5EA)                                                                                                                                                                                                                                                                                                                                     |
| 5. WiseStream II               | Support                                                                                                                                                                                                                                                                                                                                                            |
| 6. Bitrate Control Method      | H.265 / H.264: CBR or VBR                                                                                                                                                                                                                                                                                                                                          |

- |                         |                                            |
|-------------------------|--------------------------------------------|
|                         | MJPEG: VBR                                 |
| 7. Streaming Capability | Multiple streaming (Up to 10 profiles)     |
| 8. Streaming method     | Unicast / Multicast                        |
| 9. Simultaneous Users   | 20 maximum (Unicast)                       |
| 10. Profile set         | Max. 10 ea                                 |
| 11. Interoperability    | ONVIF Profile S / G, SUNAPI, Open Platform |
- F. Audio
- |                      |                                                                                                                                                 |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. Audio In          | Built in Mic / Line-in / External Mic(2.5VDC/4mA supply)<br>(Input impedance: approx. 2K Ohm)                                                   |
| 2. Audio Out         | Line out (3.5mm stereo mini jack)                                                                                                               |
| 3. Audio Compression | G.711 / G.726 / AAC Selectable,<br>G.711 u-law: 8KHz,<br>G.726 (ADPCM): 16 / 24 / 32 / 40Kbps at 8KHz,<br>AAC-LC: 48Kbps at 8 / 16 / 32 / 48KHz |
| 4. Communication     | Bi-directional (2-Way)                                                                                                                          |
- G. Network
1. Connectivity – 10/100 Base-T Ethernet via RJ-45 connector
  2. Protocol
    - a. IP v4 / v6, TCP, UDP
    - b. Configuration: DHCP, LLDP
    - c. Web service: HTTP, HTTPS
    - d. Network Service: ARP, Bonjour, DNS, ICMP, NTP, PIM-SM, SNMP v1/2c/3 – MIB-2, UPnP
    - e. Media: RTP, RTCP, RTSP
    - f. Multicast: IGMP
    - g. Notifications: FTP, SMTP
    - h. Remote Access: PPPoE
  3. DDNS – The camera shall support DDNS services offered by the manufacturer and others publicly available service offerings
  4. QoS – Layer 3 DSCP
  5. Security Feature
    - a. User password protection
    - b. The device shall not provide a manufacture default password. Default password change shall be required to access the camera.
    - c. A minimal level of password complexity shall be required by the camera.
    - d. The camera shall not have a manufacture back-door password.
    - e. The manufacturer shall provide a tool that provides the ability to make password changes to multiple cameras at the same time.
    - f. IP address filtering – List of allowed or blocked IP addresses
    - g. HTTPS(SSL) login authentication
    - h. HTTPS(SSL) secured communication
    - i. Digest login authentication

- j. User access log
  - k. 802.1x authentication
  - 6. Discovery – The manufacturer shall offer a discovery program to identify all devices of them on the network.
  - 7. Configuration – The manufacturer shall offer a configuration program that remotely allows users to change settings on multiple cameras simultaneously.
  - 8. Firmware upgrade – The manufacturer shall offer a program capable of upgrading multiple cameras at the same time (not requiring access to individual cameras).
  - 9. Camera backup setting – The manufacturer shall provide a program that provides the ability to save multiple camera settings to a file and restore these camera settings if needed.
  - 10. Reporting – The manufacturer shall provide a tool that can generate a report including thumbnail view, MAC address, IP address, serial number and other camera settings.
- H. Electrical
- 1. Power
    - a. Input Voltage / Current PoE (IEEE 802.3af), DC 12V±10%
    - b. Power Consumption Max 11W (PoE), Max 9W (DC 12V)
- I. Mechanical And Environmental
- 1. Color/Material White / Aluminum
  - 2. Dimensions (W x H) Ø160 x H125mm (6.30" x 4.92")
  - 3. Weight 1.45 kg (3.2 lb)
  - 4. Mount type Surface
  - 5. Temperature
    - a. Operating -25°C ~ +60°C (-13°F ~ +140°F)
    - b. Storage -50°C ~ +60°C (-58°F ~ +140°F)
  - 6. Humidity Less than 90% RH
  - 7. Ingression Protection IP52
  - 8. Vandal Resistance IK10

END OF SECTION

## **PART 1 EXECUTION**

### **1.01 INSTALLERS**

- A. Contractor personnel shall comply with all applicable state and local licensing requirements.

### **1.02 PREPARATION**

- A. The network design and configuration shall be verified for compatibility and performance with the camera(s).
- B. Network configuration shall be tested and qualified by the Contractor prior to camera installation.
- C. All firmware found in products shall be the latest and the most up-to-date provided by the manufacturer, or of a version as specified by the provider of the VMS or NVR.
- D. All equipment requiring users to log on using a password shall be configured with user/site-specific password/passwords. No system/product default passwords shall be allowed.

### **1.03 INSTALLATION**

- A. The contractor shall carefully follow instructions in documentation provided by the manufacturer to insure all steps have been taken to provide a reliable, easy-to-operate system.
- B. All equipment shall be tested and configured in accordance with instructions provided by the manufacturer prior to installation.
- C. Before permanent installation of the system, the contractor shall test the system in conditions simulating the final installed environment.

### **1.04 STORAGE**

- A. The hardware shall be stored in an environment where temperature and humidity are in the range specified by the manufacturer.

END OF SECTION