

SC-17P



A cost-effective 17" surveillance display with the quality, connectivity and performance essential for any security environment.

With the AG Neovo SC-17P, security centres can keep an eye on budgets without losing sight of performance. Digital and analogue video inputs, including looping BNC I/O, minimise installation cost. Auto NTSC/PAL detection, settings key lock and auto settings adjustment reduce maintenance hassle. Quick signal-switching and rapid response time improve surveillance efficiency, while built-in speakers provide an additional level of security. All this and more make the SC-17P the perfect value display choice for any security environment.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, S-Video, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -2° ~ 20°
- > Rigorous screening of the components for mission-critical 24/7 applications
- > Kensington® Security socket



SC-17P

Specifications		SC-17P
Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	17.0" (432 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	250 cd/m ²
	Contrast Ratio	1000:1
	Viewing Angle (H/V)	170°/160°
	Display Colour	16.7M
	Response Time	3 ms
Horizontal Resolution	TV Lines	600TVL (NTSC), 600TVL (PAL)
	Frequency (H/V)	H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In	3.5ø mm audio jack
	Audio Out	3.5ø mm audio jack
	Speaker	1W x 2
Power	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 18 W (On) < 0.5 W (Off)
Plug & Play	VESA	EDID
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPI	Yes (100 x 100mm)
Tilt	Tilt	-2° ~ 20°
Dimensions	Product (W x H x D)	372 x 385.2 x 184mm (14.6" x 15.2" x 7.2")
	Packaging (W x H x D)	450 x 467 x 138mm (17.7" x 18.4" x 5.4")
	Weight	Product Weight Packaged Weight
Regulation Approval	Certifications & Compliance	CB, FCC, CE, REACH, GOST-R, WEEE, RoHS
Accessories	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out

