

## SC-19P



A value 19" surveillance display with rapid response time, quick signal-switching and robust video support for security and control centre environments.

For a cost-effective surveillance display solution, look no further than the AG Neovo SC-19P. A bright, high resolution full colour screen with quick signal-switching and 7ms response time ensures sharp, smooth video playback. Looping BNC video inputs and NTSC/PAL support maximise flexibility for system integration. And with built-in speakers, stylishly slim profile and VESA mountability, the SC-19P will look just as attractive as its amazingly affordable price.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, S-Video, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time ( ≤ 0.8 sec. )
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -2° ~ 20°
- > ADS panel offers wide viewing angles up to 178 degrees
- > Rigorous screening of the components for mission-critical 24/7 applications
- > Kensington® Security socket



# SC-19P

## Specifications

## SC-19P

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	19.0" (482.6mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294 mm
	Brightness	250 cd/m <sup>2</sup>
	Contrast Ratio	1000:1
	Viewing Angle (H/V)	178°/178°
	Display Colour Response Time	16.7M 7ms
Horizontal Resolution	TV Lines	600TVL (NTSC), 600TVL (PAL)
Frequency (H/V)		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In	Stereo audio jack for PC (3.5mm)
	Audio Out	Stereo audio jack for PC (3.5mm)
	Speaker	1W x 2
Power	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 20 W (On) < 0.5 W (Off)
Plug & Play	VESA	EDID
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-2° ~ 20°
Dimensions	Product (W x H x D)	418.4 x 412 x 184mm (16.5" x 16.2" x 7.2")
	Packaging (W x H x D)	464 x 585 x 121mm (18.3" x 23.0" x 4.8")
Weight	Product Weight	3.6 kg (7.9 lbs)
	Packaged Weight	4.4 kg (9.7 lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, BSMI, GOST-R, WEEE, RoHS
Accessories	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out

