

SC-24



LED 

A high performance work-based 24" display designed for surveillance use featuring clear images and greater flexibility, the SC-24 is another fine addition to AG Neovo's line of surveillance displays.

The SC-24 features Anti-Burn-in™ technology which is ideal for displays that show the same uninterrupted images for an extended period of time. Built-in image enhancing tools allow the SC-24 to improve overall image clarity, while quick signal-switching ensures seamless video feeds. Versatile ports complemented by looping BNC in/outputs for multiple connections, help make the SC-24 adaptable to various surveillance settings based on particular needs. Finally NTSC/PAL auto-detection and auto settings adjustment increase the SC-24's ease-of-use. These features and more make the SC-24 another fine addition to AG Neovo's line of surveillance displays.

- > FHD 1920 × 1080 resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (BNC in/out, S-Video, VGA, HDMI, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount
- > Tilt capacity from -2° ~ 13°
- > Rigorous screening of the components for mission-critical 24/7 applications
- > Kensington® Security socket



SC-24

Specifications

SC-24

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	24"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.276 mm
	Brightness	250 cd/m ²
	Contrast Ratio	1000:1
	Viewing Angle (H/V)	170°/160°
	Display Colour	16.7M
	Response Time	3ms
Horizontal Resolution	TV Lines	600TVL (NTSC), 600TVL (PAL)
Frequency (H/V)		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In	Stereo audio jack (3.5 mm) x 1
	Audio Out Speaker	Stereo audio jack (3.5 mm) x 1 1W x 2
Power	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 25 W (On) < 0.5 W (Off)
Plug & Play	VESA	EDID
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-2° ~ 13°
Dimensions	Product (W x H x D)	577 x 407 x 224mm (22.7" x 16.0" x 8.8")
	Packaging (W x H x D)	626 x 453 x 116mm (24.6" x 17.8" x 4.6")
Weight	Product Weight	3.6 kg (7.9 lb)
	Packaged Weight	4.95 kg (10.9 lb)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, GOST-R, WEEE, RoHS
Accessories	Supplied	User manual, power cord, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out

