

HDCVI

High Definition Composite Video Interface



Coppia di ricetrasmittitori passivi video HDCVI monocanale su singola coppia UTP, portata 400mt a 720p o 250 a 1.080p, 200mt a 4Mp con attacco BNC maschio e cavo da 8cm + 1 RJ45 e morsettiera.

PIXVIDEO

CARATTERISTICHE TECNICHE

Model	ACE504
Properties	
Transmission Signal	1 channel
Transmission Distance	HDCVI
	720P: max.400m(1312.34ft)
	1080P: max.250m(820.21ft)
	4MP: max.200m(656.17ft)
Category Type	UTP CAT 5E/6
Video Transmission Properties And Port	
Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Push-terminal
Compatible Format	HDCVI/AHD/TVI/CVBS
Resolution	720P/1080P/4MP
Anti-interference	> 60db
Protection	
ESD	1a contact discharge electricity level 3
	1b air discharge electricity level 3 Per: IEC61000-4-2
Coaxial Cable Connector	2KV(common-code) Per: IEC1000-4-5
UTP Cable Connector	2KV(different-code), 4KV(common-code), Per: IEC1000-4-5
Impedance	
BNC Male	75 ohms
UTP Cable	100 ohms
Physical Properties	
Dimension(L*W*H)	173mm*21mm*20mm(6.81"x0.83"x0.79")
Shell	ABS
Color	Black
N.W.	25g(0.06lb)
Stability	
MTBF	> 10000h
Environmental	
Operating Temperature	-10°C~+55°C(14°F~131°F)
Storage Temperature	-20°C~+70°C(-4°F~158°F)
Humidity	0~95%(non-condensing)