



Switch di rete

Switch di rete industriale su barra DIN con 8 porte 10/100Mbps, porta 1 e 2 PoE con 30W max ciascuna (totale Massimo 93W), 8 porte PoE autosensing, 1 porta 1.000 Mps, 1 porta SFP, alimentazione 53Vdc, con alimentatore in dotazione. Supporta il backup a doppia alimentazione. (150.0x100.0x42.0mm)

PIXVIDEO

CARATTERISTICHE TECNICHE

Technical Specification

Model	ACE080PD
General	
Ethernet Port	1*1000 Base-X 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply)
PoE Power Consumption	Port1-2≤60W, Port3-8≤30W, Total≤96
PoE PIN Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
PoE Power Management	Support
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	7.6G
Packet Forwarding Rate	4.17Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Flow Control	Enable by default
Application Humidity	5%~95%
Power	DC 48~57V power adapter
Lightning Protection	Common Mode 6KV Differential Mode 4KV
ESD Protection	Air Discharge 15KV Contact Discharge 8K
Working Temperature	-30°C~65°C
Weight	540g
Dimensions	150mm×100mm×42mm