

PIX-KBF3-8CH-4T

KIT IP composto da:
n.1 NVR 8 canali IP WIFI e n.4 telecamere Bullet IP da 3 Mp



- Videoregistratore di rete wireless 5MP/3MP/1080P/720P
- Modulo Wifi integrato con alte prestazioni e alta stabilità
- Connessione automatica tra NVR e IPC
- Supporta anteprima video video/ registrazione/ riproduzione/ backup
- Supporta l'uso misto di wireless e filo, supporta scene diverse
- Supporta accesso Android/IOS/PC Remoto
- Telecamere con visione notturna I.R. max.30 metri

KIT IP composto da n.1 NVR 8 canali IP WIFI e n.4 telecamere Bullet IP da 3 Mp, H.265/H.264, uscite video principali (HDMI, VGA), predisposto per montaggio di 1 disco SATA fino a 6TB, 1 porta USB, 1 LAN 10/100Mbps + Wifi 802.11b/g/n per connessione WIFI diretta su apparati compatibili con doppia antenna, visibile da iPhone, iPad, Android, alimentazione esterna a 12Vdc (alimentatore in dotazione), compatibile ONVIF, con HD da 1TB installato. mouse in dotazione, (260.0 x 225.0 x 45.0 mm).

Camera IP Bullet WIFI, da esterno/interno IP66, risoluzione 3Mp a 25Fps, H.265/H.264, sensore CMOS progressivo 1/3", ICR meccanico, ottica 4 mm, luminosità 0.01 Lux/F1.2 (0,001 Lux con IR on), led IR portata fino a 20-30mt, 1 LAN 10/100Mbps + Wifi 802.11b/g/n, WDR. Alimentazione 12Vdc (alimentatore in dotazione), in dotazione staffa di fissaggio, compatibile ONVIF.

Dimensioni: (200.0mm x 65.0mm).

Wireless NVR		
Video and audio input	Network audio and video input	8CH
Video and audio output	HDMI output	1CH Resolution: 1024x768, 1280x1024, 1440x900, 1920x1080, Support audio output
	VGA output	1CH, Resolution: 1024x768, 1280x1024, 1440x900, 1920x1080p
Video decoding standard	H.264, H.265	
Audio decoding format	G711A	
Video and audio codec parameters	Resolution	5MP/3MP/1080P/720P
	Synchronized playback	4CH@3MP 2CH@5MP
Video management	Recording mode	Timing recording, Motion detection recording, Alarm recording
	Playback mode	Regular playback, event playback
HDD	Backup mode	U disk backup
	Type	1 SATA interface
	Max capacity	Support cloud storage or HDD with a maximum capacity of 6TB
External interface	Network Interface	1 RJ45 10M/100M adaptive Ethernet port 1 built-in wireless network card
	Antenna interface	2.4G integrated antennas
	USB interface	1 USB2.0 (optional 2 USB 2.0)
Others	Audio port	1 3.5mm headphone port (optional speaker amplifier output)
	Power	DC 12V2A
	Power consumption (without HDD)	≤5W

PIX-KBF3-8CH-4T

KIT IP composto da:
n.1 NVR 8 canali IP WIFI e n.4 telecamere Bullet IP da 3 Mp

Wireless Camera		
Technical Parameters	Model	PIX-NBF301W
	Sensor	1/3" Progressive Scan Sensor
	Resolution	3MP
	Minimum illumination	Color: 0.01 Lux; B/W: 0.001 Lux
	Shutter	1/25s to 1/25,000s
	Lens	4mm
	OSD	Date Time & Title
	White Balance	Auto
	Day&Night	Auto / Color / BW
	3D-DNR	Auto
	Mirror/Flip	On/Off
	Smart stream	Dual-stream: 2304*1296@15fps 800*448@15fps
	S/N	> 39.1 Db
	Interface	RJ45 / WIFI 802.11b/g/n
General Specification	Anti-thunder Level	Standard IEC61000-4-5
	Working Temperature/Humidity	-10°C to +50°C / 30% to 80% RH
	Working Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
	Power Input	DC12V-1A
	Power consumption	≤6W
	Size	65*200mm
	Weight	500g
	Level of Protection	IP66