


40M IR MOTORIZED VF BULLET CAMERA

I4-340IP5MVF



- 1/3" CMOS Sensor
- 4 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR / BLC / HLC
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- Analytics Support
- 3.3-12mm Motorized Lens with Auto-Focus
- 40m IR Illumination
- PoE Support
- Local Storage
- RS-485
- I/O
- 2 Way Audio
- Technician Port
- IP 66 Protection
- RS-485

Specifications

Camera	Video	Model	I4-340IP5MVF
		Image Sensor	1/3" CMOS (16:9)
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
	Audio	Min. Illumination	Day: 0.045lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
		Audio compression	G.711A/G.711U
		Communication	Two-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
		Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
		Noise Reduction	True WDR (120dB, HFR* Disabled) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
Compression	Motion Detection	Yes	
	Analytics	Pro Level	
	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-Stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
Others	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	40m (48 IR LED)
	Lens (Field of View)	3.3-12mm Motorized with Auto-Focus (81°-30°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
Connectivity	Dimensions	Φ109mm×284mm
	Weight(gross)	1115g
	Network	Two-way Audio
	Power	RJ45 (+PoE)
	Analog Video Output	DC Socket
	Audio Connectivity	CVBS(BNCx1)
Network	SD Card	1Ch Input, 1Ch Output
	RS485	Support Event recording over TF (128GB Max)
	Alarm	Yes
	Remote Monitoring	1Ch Input, 1Ch Output
	User Access	IE Browsing, CMS Software, Provision Cam2 Mobile App
	Network Protocol	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Others	ONVIF	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS
	Ethernet	Yes
	PoE	100Mbps
Others	Power Supply	Yes
	Work Environment	DC12V~600mA / PoE~8.5W
		-30°C~50°C, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

